4-2153449-BL | ECO SLX-6AS-BL-24



SL-Series Modular Jack, RJ45, Cat6A Shielded, Blue (24 ea/pkg)

 Part of CommScope's initiative of removing single-use plastics which also includes copper panels, jacks, cords and faceplates

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America

Portfolio NETCONNECT®

Product Type Modular jack

Product Series SLX Series

General Specifications

ANSI/TIA Category 6A

Cable Type Shielded

Color Blue

Conductor Type Solid | Stranded

Integrated Dust Cover Type None

Mounting SL Series faceplates and panels

 Outlet Type
 Standard

 Termination Punchdowns, minimum
 5 times

Termination Tool SI Termination tool

Termination Type IDC

Transmission Standards ANSI/TIA-568-C.2 | ISO/IEC 11801 Class EA

36.8 mm | 1.449 in

Wiring T568A | T568B

Dimensions

Depth

Panel Cutout, recommended 14.78 x 20.07 mm (0.58 x 0.79 in)

Panel Thickness, recommended 1.6 mm | 0.063 in

Height 16.13 mm | 0.635 in

Width 14.44 mm | 0.569 in

Compatible Cable Diameter, maximum 8.5 mm | 0.335 in

COMMSCOPE®

4-2153449-BL | ECO SLX-6AS-BL-24

Compatible Insulated Conductor Diameter, maximum 1.6 mm | 0.063 in

Contact Plating Thickness1.27 μmCompatible Conductor Gauge, solid26-22 AWGCompatible Conductor Gauge, stranded26-24 AWG

Electrical Specifications

Remote Powering Fully supports the safe delivery of power over LAN cabling described

by IEEE 802.3bt (Type 4) and complies with the unmating under electrical load requirements prescribed by IEC 60512-99-002

PoE Durability Supports IEEE 802.3bt Type 4 (90 W) applications after 3000 plug to

jack mating cycles

Material Specifications

Contact Base Material Beryllium copper

Contact Plating Material Gold

Material Type PC+ABS | Zamak

Mechanical Specifications

Plug to Jack Mating Cycles Complies to IEC 60603-7 series

Environmental Specifications

Operating Temperature $-10 \,^{\circ}\text{C}$ to $+60 \,^{\circ}\text{C}$ (+14 $^{\circ}\text{F}$ to +140 $^{\circ}\text{F}$)

Flammability Rating UL 94 V-0

Packaging and Weights

Packaging MaterialEco-friendly, single-use plastics-free

Packaging quantity 24

Packaging Type Bag | Carton

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



<u>4-2153449-BL | E</u>CO SLX-6AS-BL-24



