



Indoor Coverage for 1900 MHz PCS Applications

Product Classification

Product Type RF repeater unit

General Specifications

Antenna Interface at Repeater SMA Female

Indoor Antenna Optional, not included

Optional Antenna Gain 2 dBi

Optional Antenna Type Omni

Performance Note Values typical, unless otherwise stated

Supervision/Control Option Heartbeat via SMS | Remote control

Dimensions

Height 240 mm | 9.449 in

Width 240 mm | 9.449 in

Optional Antenna Length 90 mm | 3.543 in

Depth 35 mm | 1.378 in

Electrical Specifications

Gain 78 dB

Gain Adjustment Range 30 dB

License Band PCS 1900

Local Power 6 Vdc

Mains Power 100–240 Vac

Return Loss 10 dB

Power Consumption 20 W

7613702 | MR1918

Electrical Specifications, Rx (Uplink)

Operating Frequency Band	1850 – 1910 MHz
Output Power @ One Carrier	22 dBm (CDMA) 22 dBm (GSM)
Output Power @ Two Carriers	19 dBm (CDMA) 19 dBm (GSM)

Electrical Specifications, Tx (Downlink)

Operating Frequency Band	1930 – 1990 MHz
Output Power @ One Carrier	22 dBm (CDMA) 22 dBm (GSM)
Output Power @ Two Carriers	19 dBm (CDMA) 19 dBm (GSM)

Environmental Specifications

Operating Temperature	+5 °C to +40 °C (+41 °F to +104 °F)
Ingress Protection Test Method	IEC 60529:2001, IP30

Packaging and Weights

Weight, net	1.5 kg 3.307 lb
--------------------	-------------------

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

