DB992HG28N-B



1-port small cell antenna, 1710–2490 MHz, 30° HPBW, fixed electrical tilt

- High gain array ideal for point-to-point and repeater applications
- Unique mounts allow vertical or horizontal polarization

General Specifications Antenna Type Small Cell Band Single band Color Light Gray (RAL 7035) **Grounding Type** RF connector inner conductor and body grounded to reflector and mounting bracket **Performance Note** Outdoor usage **Radome Material** ABS. UV resistant **Radiator Material** Aluminum **RF** Connector Interface N Female **RF Connector Location** Bottom **RF** Connector Quantity, high band 1 **RF** Connector Quantity, total 1 Dimensions Width 311 mm | 12.244 in Depth 124 mm | 4.882 in Length 311 mm | 12.244 in Net Weight, without mounting kit 1.3 kg | 2.866 lb **Electrical Specifications** Impedance 50 ohm **Operating Frequency Band** 1710 - 2490 MHz Polarization Horizontal | Vertical | Vertical **Electrical Specifications Frequency Band, MHz** 1710-2170 2170-2490

16

Gain, dBi

©2023 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: October 25, 2023



16

DB992HG28N-B

Beamwidth, Horizontal, degrees	28	28
Beamwidth, Vertical, degrees	30	30
Beam Tilt, degrees	0	0
USLS, typical, dB	15	15
Front-to-Back Ratio at 180°, dB	30	30
VSWR Return loss, dB	1.4 15.6	1.9 10.1
PIM, 3rd Order, 2 x 10 W, dBc	-150	-150
Input Power per Port, maximum, watts	100	100

Mechanical Specifications

Wind Loading @ Velocity, maximum	156.0 N @ 150 km/h (35.1 lbf @ 150 km/h)
Wind Speed, maximum	201 km/h (125 mph)

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant
	2015

Included Products

DB390

Pipe Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Use for narrow panel antennas. Includes two pipe mounts.

* Footnotes

Performance Note

e Severe environmental conditions may degrade optimum performance

Page 2 of 2

©2023 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: October 25, 2023

