

HW4X-6516DS1-VTM



8-port sector antenna, 8x 1710–2690 MHz, 65° HPBW, RET compatible

- Provides a future-ready antenna solution with flexibility to reassign antenna, for example GSM 1800 service to 2.6GHz LTE at a later date
- Employs state-of-the-art ultra wideband technology providing excellent RF performance in all bands
- Width of 2 pieces of HWXX-6516DS1 placed side by side is 610 mm, strapping them leads to a total width of 628 mm (end to end)

OBSOLETE

This product was discontinued on: **March 31, 2023**

General Specifications

Antenna Type	Sector
Band	Single band
Color	Light Gray (RAL 7035)
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	PVC, UV resistant
Radiator Material	Low loss circuit board
Reflector Material	Aluminum
RF Connector Interface	7-16 DIN Female
RF Connector Location	Bottom
RF Connector Quantity, high band	8
RF Connector Quantity, mid band	0
RF Connector Quantity, low band	0
RF Connector Quantity, total	8

Dimensions

Width	628 mm 24.724 in
Depth	118 mm 4.646 in
Length	1390 mm 54.724 in
Net Weight, without mounting kit	23 kg 50.706 lb

HW4X-6516DS1-VTM

Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1710 – 2690 MHz
Polarization	±45°
Total Input Power, maximum	900 W @ 50 °C

Electrical Specifications

Frequency Band, MHz	1710–1880	1850–1990	1920–2170	2300–2500	2500–2690
Gain, dBi	17.3	17.6	18	18.6	18.6
Beamwidth, Horizontal, degrees	68	67	67	62	63
Beamwidth, Vertical, degrees	6.7	6.4	6.1	5.3	5
Beam Tilt, degrees	0–10	0–10	0–10	0–10	0–10
USLS (First Lobe), dB	16	16	16	19	19
Front-to-Back Ratio at 180°, dB	31	31	32	32	30
Isolation, Cross Polarization, dB	30	30	30	30	30
Isolation, Inter-band, dB	28	28	28	28	28
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-150	-150	-150	-150	-150
Input Power per Port, maximum, watts	350	350	350	300	300

Mechanical Specifications

Wind Loading @ Velocity, frontal	1,024.0 N @ 150 km/h (230.2 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	120.0 N @ 150 km/h (27.0 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	1,120.0 N @ 150 km/h (251.8 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

Packaging and Weights

Width, packed	718 mm 28.268 in
Depth, packed	249 mm 9.803 in
Length, packed	1706 mm 67.165 in
Weight, gross	36.5 kg 80.469 lb

HW4X-6516DS1-VTM

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



Included Products

- BSAMNT-3 – Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance