

LLPX210R-V1



4-port sector antenna, 4x 2300–2700 MHz, 33° HPBW, 2x RET with manual override

- Excellent upper sidelobe suppression

General Specifications

Antenna Type	Sector
Band	Single band
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	ASA, UV stabilized
Radiator Material	Low loss circuit board
Reflector Material	Aluminum
RF Connector Interface	7-16 DIN Female
RF Connector Location	Bottom
RF Connector Quantity, high band	4
RF Connector Quantity, mid band	0
RF Connector Quantity, low band	0
RF Connector Quantity, total	4

Remote Electrical Tilt (RET) Information

RET Interface	8-pin DIN Male
RET Interface, quantity	2 male
Input Voltage	10–30 Vdc
Internal RET	High band (2)
Power Consumption, idle state, maximum	2 W
Power Consumption, normal conditions, maximum	13 W
Protocol	3GPP/AISG 2.0 (Single RET)

Dimensions

Width	610 mm 24.016 in
--------------	--------------------

LLPX210R-V1

Depth	115 mm 4.528 in
Length	1077 mm 42.402 in
Net Weight, without mounting kit	14.5 kg 31.967 lb

Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	2300 – 2700 MHz
Polarization	±45°

Electrical Specifications

Frequency Band, MHz	2300–2500	2500–2700
Gain, dBi	20.1	20.2
Beamwidth, Horizontal, degrees	34	31
Beamwidth, Vertical, degrees	7.3	6.8
Beam Tilt, degrees	0–10	0–10
USLS (First Lobe), dB	22	19
Null Fill, dB	-22	-22
Front-to-Back Ratio at 180°, dB	33	33
Isolation, Cross Polarization, dB	30	30
VSWR Return loss, dB	1.43 15.0	1.43 15.0
PIM, 3rd Order, 2 x 20 W, dBc	-150	-150
Input Power per Port, maximum, watts	250	250

Mechanical Specifications

Wind Loading @ Velocity, frontal	862.0 N @ 150 km/h (193.8 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	70.0 N @ 150 km/h (15.7 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	889.0 N @ 150 km/h (199.9 lbf @ 150 km/h)
Wind Speed, maximum	200 km/h (124 mph)

Packaging and Weights

Width, packed	693 mm 27.283 in
Depth, packed	221 mm 8.701 in
Length, packed	1285 mm 50.591 in
Weight, gross	32 kg 70.548 lb

LLPX210R-V1

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

Classification

Designed, manufactured and/or distributed under this quality management system

Included Products

T-045-GL-E

- Adjustable Tilt Pipe Mounting Kit for 2.0"-4.5" (60-115mm) OD round members for panel antennas. Includes 2 clamp sets.

* Footnotes

Performance Note

Severe environmental conditions may degrade optimum performance