810009835/DB | 0-012-CA-8W-M12BK/GY/HD



Fiber OSP cable, 12-fiber, OS2, HDPE, loose tube, 12 fiber, gel-filled, Singlemode G.652.D and G.657.A1, 1000 m, Meters jacket marking, Black jacket color

Product Classification

Regional Availability Australia/New Zealand | EMEA

PortfolioCommScope®Product TypeFiber OSP cable

Product Series O-CA

General Specifications

Armor Type Corrugated steel

Cable TypeLoose tubeSubunit TypeGel-filled

Filler, quantity 1

Jacket ColorBlackJacket MarkingMetersJacket Marking MethodInkjet

Jacket Marking Text COMMSCOPE GB SYSTEM F.O. CABLE 810009835/DB CSA GEL LOOSE TUBE 12X9

/125 OS2 HDPE (Serial NUMBER) (METRE MARK)

Fibers per Subunit, quantity 12

Total Fiber Count 12

Dimensions

 Cable Length
 1000 m | 3,280.84 ft

 Diameter Over Jacket
 10 mm | 0.394 in

Material Specifications

Jacket Material High density polyethylene (HDPE)



810009835/DB | 0-012-CA-8W-M12BK/GY/HD

Mechanical Specifications

Minimum Bend Radius, loaded150 mm5.906 inMinimum Bend Radius, unloaded100 mm3.937 inTensile Load, long term, maximum1250 N281.011 lbf

Flex 25 cycles

Optical Specifications

Fiber Type G.652.D and G.657.A1

Optical Specifications, Wavelength Specific

Attenuation, maximum 0.35 dB/km @ 1,300 nm | 0.35 dB/km @ 1,550 nm | 0.45 dB/km @ 1,310 nm

Standards Compliance IEC 60794-1 | TIA-492CAAB (OS2)

Environmental Specifications

Installation temperature $-5 \,^{\circ}\text{C}$ to $+50 \,^{\circ}\text{C}$ (+23 $^{\circ}\text{F}$ to +122 $^{\circ}\text{F}$)

Operating Temperature $-20 \,^{\circ}\text{C}$ to $+70 \,^{\circ}\text{C}$ (-4 $^{\circ}\text{F}$ to +158 $^{\circ}\text{F}$)

Storage Temperature $-20 \,^{\circ}\text{C}$ to $+70 \,^{\circ}\text{C}$ (-4 $^{\circ}\text{F}$ to +158 $^{\circ}\text{F}$)

Packaging and Weights

Cable weight 104 kg/km | 69.885 lb/kft

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



Included Products

DB-8W-LT – LightScope ZWP® Singlemode Fiber

* Footnotes



810009835/DB | 0-012-CA-8W-M12BK/GY/HD

Operating Temperature Specification applicable to non-terminated bulk fiber cable