108168477 | M12L-246



L Type Flush Mounted Faceplate, 2 port, ivory

• Available for use with the DYMO® labeling solution

OBSOLETE

Replaced By:

760249169 FP-LBL-2P-246

Faceplate Kit, Labelled, 1-gang, 2 port, electric ivory

Product Classification

Regional Availability Asia | Australia/New Zealand | EMEA | Latin America | North America

PortfolioCommScope®Product TypeFaceplate kitProduct SeriesM Series

Todact oches

General Specifications

Application Used with M Series modular information outlet

ColorIvoryMountingFlushTotal Ports, quantity2

Dimensions

 Height
 115.824 mm | 4.56 in

 Width
 71.374 mm | 2.81 in

 Depth
 7.366 mm | 0.29 in

Material Specifications

Material Type High-impact, flame retardant, thermoplastic

Environmental Specifications

Flammability Rating UL 94 V-0

COMMSCOPE®

108168477 | M12L-246

Safety Standard UL | cUL

Packaging and Weights

Packaging quantity 1

Weight, net 0.041 kg | 0.09 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant

