760255091 | PPL-SP-16LC-0M5-PT-BEU-ANT

Propel Multimode Splice Cassette, 16LC with internal shutters, OM5 single fiber pigtails, Method B Enhanced ULL, ANT Splice Protector

- Can be installed and removed from front or rear of panel
- This component requires 4 of the 12 lanes on the Propel Panel blade

Product Classification

Regional Availability Europe

Portfolio SYSTIMAX®

Product Type Fiber cassette with pigtails

Product Brand Propel
Product Series PPL

General Specifications

Color, front Lime green
Interface, front LC/UPC

Interface, rear Stranded pigtail

Polarity Method B Enhanced (ULL)

Shuttered Yes

Total Fibers, quantity 16

Dimensions

 Height
 67.31 mm | 2.65 in

 Width
 131.013 mm | 5.158 in

Optical Specifications

Fiber ModeMultimodeFiber TypeG.657.A2Insertion Loss, maximum0.15 dB

Environmental Specifications

Qualification Standards IEC 61753-1 | TIA-568.3-D

Safety Standard UL

Page 1 of 2

760255091 | PPL-SP-16LC-0M5-PT-BEU-ANT

Packaging and Weights

Included Single Fusion Splice Protection Sleeves

Packaging quantity 1

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant

